GPS RAIM Prediction Service



FAA's Operational Tool GPS Navigation Predictions in the Flight Planning Process

Dr. Andrew Hansen, Jon Parmet, Chris Dufresne & Nathan Buckley Karen VanDyke, USDOT /RITA

Serving the Nation as a leader in global transportation innovation since 1970

23 June 2010













GNSS Service Availability Prediction


Operational Mission Planning Tools


--Anticipate Service Outages

--Mitigate Continuity Breaks

-- Enable Graceful Degradation

--Improve User Acceptance







US FAA GPS RAIM Prediction Service Overview


Early Motivation:

AC90-100A establishes rule for pre-flight check of GPS navigation

- Modeling and Prediction Function
 - Provide location-based information on expected availability of GPS navigation services
 - Account for active state of GPS constellation
 - Evaluate availability of require navigation performance (RNP) service against certification models (initially, FAA TSO-C129)
- Web based Service: http://www.raimprediction.net
 - Two primary interfaces:
 - -- Interactive, graphical display via web browser
 - -- Procedural, XML protocol on tcp/ip stack
 - "Live" monitoring of the SVN constellation via GPS Almanac, SV NOTAM, and US DoD NANU



GPS RAIM Prediction Service Network






Interactive GPS RAIM Service Interface

- Nominally 24/7 Web Access via Browser
- Reads Out Three Levels of RNP Service (all horizontal)
 - En Route (HAL < 2 nmi)</p>
 - Terminal Area (HAL < 1 nmi)</p>
 - Non-precision Approach (HAL < 556m)</p>
- Graphical Display
 - Interactive URL http://www.raimprediction.net
 - Service volume (US NAS)—1x1 degree (0.5 x 0.5 for NPA) grid
 - Time resolution is 1 min sampling of the GPS constellation with 6 min outage threshold
- System Auto-Refreshes on Any Constellation Change
 - New almanac issued
 - SV NOTAM issued or cancelled
 - NANU issued or cancelled




Interactive Interface (Web Browser Display)








Interactive Interface (Playback Modes)





Interactive Interface (Zoom/Pan/Select)







Procedural GPS RAIM Service Interface

RAIMWebServiceSOAP Interface Control Document (ICD)

➤ Schema Advertised via Web Service Definition Language

(WSDL)

➤Inputs:


Trajectory of 4D points

Desired RNP level

Avionics configuration


➤Outputs:

Echo of input data
Diagnostic information
Point-by-point indication
of any predicted outages
(HPL > HAL)





Procedural GPS RAIM Service Interface





GPS RAIM Prediction Service

Operational Statistics Since Deployment (1 Jul 2009)

- 8 million+ Transactions Served
- Response Time Performance (< 5 Second Transactions)
- User Adoption
 - Carriers/Operators: Horizon, NetJets, Continental, JetBlue, Delta
 - > Vendors/Dispatchers: DUATS, WSI, Sabre
- Primary Demand Is Trajectory Based Operations (Procedural Interface)



Conclusions

- Service Availability Predictions Important Factor in Adoption of GNSS Services
 - Gives users confidence and additional convenience
 - Assists service providers with automated forward looks at service volume performance
 - Improves conditions for safety of operations via planning
- Customized Prediction Services
 - > Presentation and interface options
 - Selection of models (nominally TSO specifications)
 - Access control, secure connection, transaction history, etc.
- Sponsor Acknowledgement on AC90-100A Effort:
 Lou Volchansky FAA–AIR/NavTeam

